



NEWS FROM GAM

FOR IMMEDIATE RELEASE

For more information contact:

Gary Michalek

GAM

Telephone: (847) 649-2500

Email: gary@gamweb.com

Website: www.gamweb.com

Twelve Types of Bellows Couplings Featured in New GAM Selection Guide

Mount Prospect, IL, USA, 23 July 2008 – GAM's complete line of bellows couplings for servo applications are among the products detailed in a new full-line brochure from GAM. An easy-to-follow product selection chart – also available at www.gamweb.com -- guides users through bore and torque ranges, hub style, bellows connection method and other major features for each series in the product line.

Select couplings offer several unique features. GAM's patented EASY Clamp System prevents damage to hubs and allows easy shaft mounting/dismounting while compensating for tolerance differences between shaft and hub. The patented brass wire press-fit method of connecting the multi-layered bellow to the hub can withstand high-temperature and harsh chemical environments where glued connections cannot. The micro plasma weld connection offers even heat distribution which results in a long-lasting connection between hub and bellow and is ideal for high temperature applications.

GAM's bellows couplings are available with torque ratings from 0.44 Nm to 44,000 Nm for use with servo motors. All feature high torsional rigidity, low inertia, zero backlash and misalignment compensation. They can be used maintenance-free at temperatures up to 570°F without any limitations and at speeds up to 25,000 RPM without additional balancing.

GAM offers same day delivery on several standard and custom bored couplings.

For more information on GAM's full line of gear reducers, linear slide kits, servo couplings and safety couplings, contact GAM, 901 E. Business Center Drive, Mount Prospect, IL 60056, Telephone (847) 649-2500, FAX (847) 649-2501.

###